




# HEAVY DEALS

2025-1



SLOVAKIA s.r.o.

**INTOOL**

**TecDoc**  
DATA SUPPLIER

EINFACH VIGOR.

Valid from 01/04/2025 to 28/02/2026 – errors excepted



HEAVY25/EN/XX/0

**V8663**

EAN 4047728086639

## Commercial vehicle ball joint puller for tight installation spaces

- Compact puller for removing ball joints in tight installation spaces, e.g. on **SCANIA** Next Generation trucks



**New**



*Enables quick removal without time-consuming removal of surrounding components!*



5



**V8664**

EAN 4047728086646

## Expansion set ball joint puller for 8.5 t cylinder V2873

- Cylinder not included in the set



**New**

4



**V2920**

EAN 4047728029209


## Ball joint puller · universal

- For removing the ball joint pivots from steering arms on vans, trucks and buses
- Slim construction – for **MERCEDES-BENZ** Sprinter and **FORD** Transit ball joints
- V2873 compressive and tractive hydraulic cylinder 8.5 tonnes, available separately



Cylinder not included in delivery

V2873



*Impact function to multiply the pressing force up to 25.5 tonnes of compressive force!*

1







**V5916-XL**EAN 4047728**066471****Ball joint ejector**

- For the hydraulic removal of the ball joint pivots on steering tie rods as well as stabilisers, or steering and brake levers on trucks and buses, with a maximum compressive force of 8.8 tonnes
- Pressing out and pressing in of wheel bolts possible

# 8.8 t


pressing  
force



3

**V5912**EAN 4047728**059374****Universal puller for steering arms**

- Adjustable puller with universal application, for loosening almost all spherical joint bearings and steering arms
- Can be used in combination with an 18- or 22-tonne hydraulic cylinder V4551 or V2854
- The wedge-shaped press feet allow optimum access for separating components
- Time saving and risk minimisation through direct application on the vehicle



9



VIGOR No.	Designation	EAN 4047728+
<b>V5912-1</b>	Pressure foot, 2 pieces	<b>059381</b>
<b>V5904-3</b>	Sliding plate	<b>059138</b>
<b>V5904-4</b>	Screw · M14 x 2 – 45 · inside hexagon	<b>059145</b>




**V2867N**

 EAN 4047728**077859**

## Circlip tool

- Removal of internal circlips in wheel bearings
- For passenger cars, vans and trucks
- Sophisticated design covers all working angles and circlip sizes
- Quick changing of spare tips

**The circlip tool**  
**during application** ➤



Ø 2.5 mm

Ø 3.0 mm

Ø 3.5 mm



## Spare pins for V2867N

VIGOR No.	Designation		EAN 4047728+
<b>V2992</b>	Pin Ø 2.5 mm	2	<b>029926</b>
<b>V2993</b>	Pin Ø 3.2 mm	2	<b>029933</b>
<b>V2994</b>	Pin Ø 3.5 mm	2	<b>029940</b>



7


**V2846**

 EAN 4047728**028462**

## Pneumatic hydraulic foot pump


- Convenient and direct operation thanks to pneumatic support and highly sensitive foot pedal
- Pressure gauge shows working pressure
- Robust housing protects high-quality built-in components


**V2847**

 EAN 4047728**028479**

## Mechanical hydraulic foot pump

- Stands securely and solidly on its feet
- Robust steel body
- Foot-operated – no pneumatic connection required and thus flexible and mobile in use
- Ideal for mobile use



VIGOR No.	Designation	EAN 4047728+
<b>V3120</b>	2.2 m hydraulic hose 1/4"	<b>031202</b>
<b>V3141</b>	(CEJN) quick coupler connection	<b>031417</b>





**V2873**

EAN 4047728028738

## Tractive and compressive hydraulic cylinder 8.5 tonnes

- Pressing out supporting joints and bushings
- For operation in areas with restricted access
- Thrust rod adjustable

**Impact function to multiply the pressing force up to 25.5 tonnes of compressive force!**





**V2869**

EAN 4047728028691

## Compressive hydraulic cylinder 14 tonnes

- Pressing out supporting joints and bushings
- Especially for use with the press frames V2885 and V2858N



**V4551**
**EAN 4047728045513**

## Tractive and compressive hydraulic cylinder 18 tonnes


- Pressing out rusted drive shafts
- Pressure of the hydraulic cylinder may be combined with impact force when using an impact body
- To be used with all passenger car tools and drawbars M10 – M22 with an appropriate reduction



**Extra light:  
Only 2.8 kg**



**Impact function to multiply  
the pressing force up to  
63 tonnes of compressive force!**



**10**
**V2854**
**EAN 4047728028547**

## Tractive and compressive hydraulic cylinder 22 tonnes

- Pressing out rusted drive shafts
- Pressure of the hydraulic cylinder may be combined with impact force when using an impact body
- To be used with all passenger car tools and drawbars M10 – M22 with an appropriate reduction



**Impact function to multiply  
the pressing force up to  
77 tonnes of compressive force!**



**10**
**V2874**
**EAN 4047728028745**

## Tractive and compressive hydraulic cylinder 32 tonnes

- Pressing out rusted drive shafts and king pins
- Pressure of the hydraulic cylinder may be combined with impact force when using an impact body
- To be used with all passenger car tools and drawbars M10 – M22 with an appropriate reduction
- The stroke makes it particularly suitable for replacing axle bushings



**Impact function to multiply  
the pressing force up to  
112 tonnes of compressive force!**



**8**




**V4229**

EAN 4047728**042291**
**Tractive and compressive hydraulic cylinder 45 tonnes**

- Pressing out rusted drive shafts
- Pressure of the hydraulic cylinder may be combined with impact force when using an impact body




**Impact function to multiply the pressing force up to 157 tonnes of compressive force!**



**V8321**

EAN 4047728**083218**
**Compressive hydraulic cylinder 70 tonnes**

- 70-tonne hydraulic cylinder for commercial vehicle repair workshops
- Mainly for hub removal tools V4554, V4555 and V4500
- To be used in combination with pressing pieces V8323 and V8316
- Weight: 17 kg, stroke: 70 mm
- Automatic piston return function
- In combination with V8667, also suitable for pressing out fixing bolts and king pins




**Impact function to multiply the pressing force up to 245 tonnes of compressive force!**


**V8323**

EAN 4047728**083232**
**Pressing piece 30 mm**

- 30 mm pressing adapter for pressing out wheel hubs or steering knuckles, for example
- Only to be used together with cylinder V8321


**V8316**

EAN 4047728**083164**
**Pressing piece 200 mm**

- 200 mm pressing adapter for pressing out wheel hubs or steering knuckles, for example
- Only to be used together with the 70-tonne hydraulic cylinder V8321




**V4565**

 EAN 4047728**045650**

## Universal press frame for commercial vehicles 32 tonnes for king pins and fixing bolts

- For the majority of king pins commonly available on the market, including for tapered models
- Unique impact function enables removal with hammer strokes on the cylinder (with mounted impact body) in direction of actuation
- Very effective impact function transmits the vibrations required for successful removal to the material
- Removal of the axle is not necessary
- 32 tonne-version
- Easy to use, also suitable for buses, where access is often restricted
- Also suitable for pressing in and pressing out fixing bolts on agricultural, construction and forestry machinery




10


**V4566**

 EAN 4047728**045667**

## Universal press frame for commercial vehicles 45 tonnes for king pins and fixing bolts

- For the majority of king pins commonly available on the market, including for tapered models
- Unique impact function enables removal with hammer strokes on the cylinder (with mounted impact body) in direction of actuation
- Very effective impact function transmits the vibrations required for successful removal to the material
- Removal of the axle is not necessary
- 45 tonne-version
- Easy to use, also suitable for buses, where access is often restricted
- Also suitable for pressing out and pressing in fixing bolts on agricultural, construction and forestry machinery



12






**V8318**

EAN 4047728**083188**

### Bolt press set

For removal and installation of master pins on chain links

- The mounting plate allows work to be carried out alone
- Mobile and flexible, both in the workshop and in field service
- Internal dimensions of the adapters: Ø 35 mm, Ø 39 mm, Ø 45.4 mm, Ø 48.2 mm
- Only to be used in combination with 45-tonne hydraulic cylinder V4229
- Optimum extension of king pin removal set V4565 and V4566
- Pressure pieces included in the set


**24**

**V8318-1**

EAN 4047728**083195**

### Expansion set for bolt press set

For removal and installation of master pins on chain links

- The mounting plate allows work to be carried out alone
- Mobile and flexible, both in the workshop and in field service
- Internal dimensions of the adapters: Ø 35 mm, Ø 39 mm, Ø 45.4 mm, Ø 48.2 mm
- Only to be used in combination with 45-tonne hydraulic cylinder V4229
- Optimum extension of king pin removal set V4565 and V4566
- Plates and pressure pieces not included in the set
- Length of the threaded support rods: 383 mm and 557 mm


**New**

**24**

**V8324**


EAN 4047728**083249**

### Universal press frame for pressing around fixing bolts, bushing and bearings

- Extra wide press frame for crane trucks, excavator arms or chain links
- Suitable for crane trucks to container side loaders
- To be used with 32-tonne cylinder (V2874) or 45-tonne cylinder (V4229)
- Expandable with pressure sleeve set V5914




Cylinder not included in delivery


**4**


**V8667**
**EAN 4047728086677**

## Universal press frame for commercial vehicles 70 tonnes for king pins and fixing bolts

- For the majority of king pins commonly available on the market, including for tapered models
- Unique impact function enables removal with hammer strokes on the cylinder (with mounted impact body) in direction of actuation
- Very effective impact function transmits the vibrations required for successful removal to the material
- Removal of the axle is not necessary
- 70 tonne-version
- Easy to use, also suitable for buses, where access is often restricted
- Also suitable for pressing out and pressing in fixing bolts on agricultural, construction and forestry machinery
- Strut length: 515 mm


**New**
**23**

**V8666**
**EAN 4047728086660**

## Extension set universal press frame for commercial vehicles 70 tonnes for king pins and fixing bolts

- Expansion set for 70-tonne cylinders for the universal press frames for 32-tonne and 45-tonne cylinders (V4565 and V4566)
- Strut length: 515 mm, only to be used together with plates V4556 (2x)


**New**


**Enables the use of the 70-tonne compressive cylinder**

**21**




**V4604**EAN 4047728**046046****Universal pressure tool set 45 tonnes**

- Quick changing of tapered and cylindrical king pins, drawbar bolts as well as large circlips
- Contents:
  - Removal tools for ball joints, brake adjuster, VBG-drawbar bolts
  - Tools for removing wheel hubs
  - 8.8-tonne and 45-tonne hydraulic cylinder with spindle and impact body
  - Ball joint puller V5916-XL for removing ball joints and replacing wheel bolts



**For the challenges of  
king pins, wheel hubs, joints  
and circlips - all in one!**



**V8721**

EAN 4047728087216

## Pressure tool set 70 tonnes · universal

- Quick changing of tapered and cylindrical king pins, fixing bolts of hydraulic cylinders and drawbar bolts, as well as large circlips
- Contents:
  - Removal tools for ball joints, brake adjuster, VB&G drawbar bolts
  - Tools for pressing out wheel hubs, king pins and fixing bolts
  - 8.8-tonne and 70-tonne hydraulic cylinder with pressure piece and impact body
  - Tool for removing and installing circlips



**New**



48



**V8668**

EAN 4047728086684

## Expansion set 70 tonnes for BPW and SAF king pins

- Extension set with 70 tonnes release for items V8666 and V8667
- With V4565 and V4566 as the basis, screw V3263 is required four times
- The system enables the pressing in and out of king pins on the trailer using the 70-tonne cylinder, without having to remove the axle in advance



**New**



610 mm


9






**V2858N**EAN 4047728**075268****Press frame**

- Suitable for vehicle-specific and universal applications
- Ideal for pressing out and pressing in bolts, bearings and supporting joints
- Pressing force maximum 18 tonnes

**V8669**EAN 4047728**086691****Extension set for bolts on rear hydraulics FENDT & MASSEY FERGUSON**

- Extension kit based on press frame V2858N and the 18-tonne (V4551) or 22-tonne (V2854) hydraulic cylinder for releasing the fixing bolt on the lifting hydraulics at the rear of **FENDT** models of the 500 SCR; 500 S4; 500 Gen3; 700 S4; 700 Gen6 series on which the cone mandrel (743870200110) is installed, as well as on **MASSEY FERGUSON** models of the series: MF 6700S · MF 6S · MF 7700 (S) · MF 7S · MF 8S
- Press frame and hydraulic cylinder not included
- If necessary, the bolt can also be pulled with the traction side of the cylinder in combination with the threaded rod V3220 and the threaded adapter V3219 (both not included in the set) with a maximum of 9 tonnes

**New**

**Enables a fast removal  
of the fixing bolt  
without damage!**

**V4635**EAN 4047728**046350****Spring bushing set · universal**

- Allows changing of spring bushings without unnecessary disassembly
- Including tool parts for replacing the spring-loaded joint bushing
- For bushings size 44 to 63 mm
- Easy removal, even of rusted bushings, due to impact function

**9**

**V4569**

EAN 4047728**045698**

## King pin removal expansion set

- Expansion set for the items V4565 and V4566
- The system allows the pressing in and out of king pins on trailers without removing the axle in advance



595 mm

9




**V4605**

EAN 4047728**046053**

## King pin removal expansion set for MERCEDES-BENZ Actros and Atego

- Expansion set for the items V4565 and V4566
- System allows extraction and insertion of king pins to be carried out directly on the vehicle



6




**V4606**

EAN 4047728**046060**

## Steering knuckle removal expansion set MAN TGA · TGX and TGS

- Expansion set for the items V4565 and V4566
- System allows extraction and insertion of king pins to be carried out directly on the vehicle



5



**V5917**

EAN 4047728**059831**

## Adjustable tripod mount

- The holder allows you to work at different angles
- Serves as an extension to the V4565 and V4566 press frames
- Adjustable both horizontally and vertically
- Bracket can be adapted to transmission jacks or hydraulic cylinders
- The bracket has inside diameters of 25 mm and 30 mm
- The multiple positions on the flange in combination with the swivelling head maximise access under the vehicle
- Optimised application for the press plate V4556



3



**V8315**

EAN 4047728**083157**
**Dismounting pipe for pressing out the steering knuckle of ZF axles, MERCEDES BENZ and Setra**

- The recess for the shock absorber bracket ensures optimum positioning and safe removal of the king pin
- Impressively dimensioned dismounting pipe for use with the 45-tonne cylinder V4229
- Use with press frames V4565 and V4566


**V8325**

EAN 4047728**083256**
**Adapter plate for Volvo steering knuckle bolt**

- Adapter specially designed for **Volvo** axles, cone centres the press plate during application
- Only to be used together with press frame V4550


**V8314**

EAN 4047728**083140**
**Pressure sleeve for SCANIA king pins**

- Sleeve for pressing out tapered king pins on **SCANIA** vehicles


**V2929**

EAN 4047728**029292**
**Steering knuckle removal extension for Volvo**

- Pressure piece is required for pressing out the steering knuckle on **Volvo** axles
- Pressure piece is supported on the carrier to prevent the bearing from being pressed out


**V2936**

EAN 4047728**029360**
**Bushing set · for SAF axle · 150 mm**

- Quick, easy removal / installation of the large rubber bushings 150 mm on **SAF** axles
- Recommended for use with 32 tonnes hydraulic cylinder V2874 (not included)



Length of spindle M22 - 250 mm

32t



6


**V8317**

EAN 4047728**083171**
**Extension bushing set**

- For replacing bushings on **BPW** and **ROR** axles in combination with our recommended hydraulic cylinder V2874
- Set is also the extension of item V8317 for **SAF**, **JOIST**, **MB** and **ROR** bushings with a diameter of 150 mm

**BPW and ROR bushings 119 mm and 139 mm**


32t



5





**V5066**
**EAN 4047728050661**


## Pressure sleeve set

- Adapter and pressure shaft enable application of the press frame V2885 – useful when removing or installing bushings and supporting joints without holes
- Hydraulic cylinder required



Supplied in soft foam insert!

VIGOR No.	Designation	Ø A mm	Ø B mm	Ø C mm	EAN 4047728+
<b>V2947</b>	Pressure sleeve	40.7	42.5	35.2	<b>029476</b>
<b>V2948</b>	Pressure sleeve	43.7	45.5	38.2	<b>029483</b>
<b>V2949</b>	Pressure sleeve	46.7	48.5	41.2	<b>029490</b>
<b>V2950</b>	Pressure sleeve	49.7	51.5	44.2	<b>029506</b>
<b>V2961</b>	Pressure sleeve	52.7	54.5	47.2	<b>029612</b>
<b>V2962</b>	Pressure sleeve	55.7	57.5	50.2	<b>029629</b>
<b>V2963</b>	Pressure sleeve	58.7	60.5	53.2	<b>029636</b>
<b>V2964</b>	Pressure sleeve	61.7	63.5	56.2	<b>029643</b>
<b>V2965</b>	Pressure sleeve	65.7	67.5	60.2	<b>029650</b>
<b>V2966</b>	Pressure sleeve	69.7	71.5	64.2	<b>029667</b>
<b>V2967</b>	Pressure pipe	38.7	44.7	30.5	<b>029674</b>
<b>V2968</b>	Pressure pipe	41.7	44.7	34.0	<b>029681</b>
<b>V2969</b>	Pressure pipe	44.7	44.7	37.2	<b>029698</b>
<b>V2971</b>	Pressure pipe	44.7	55.0	40.2	<b>029711</b>
<b>V2972</b>	Pressure pipe	50.7	55.0	43.2	<b>029728</b>
<b>V2973</b>	Pressure pipe	53.7	55.0	46.2	<b>029735</b>
<b>V2974</b>	Pressure pipe	56.7	55.0	49.2	<b>029742</b>



**V5914**EAN 4047728**059503****Universal pressure sleeve set with fixing unit**


- The selection of diameters of the pressure pipes and press plates makes this set very versatile for commercial vehicles, either directly on the vehicle or on the workshop press
- The mounting plate included enables the pressure pipes to be fixed to the press block. Work is made easier as fewer parts have to be positioned by hand.
- The set can be supplemented with V5913 to create a complete solution for slotted bushings
- Adapters for cylinders V2874 or V4229 are included in the set
- Hydraulic cylinder required



Supplied in Multibox V4700-XL!

Installation situation of a slotted and tensioned bushing.

V5913 or V5913/6 are required for the installation of slotted bushings.



19

	VIGOR No.	Designation	Ø A mm	Ø B mm	Ø C mm	Length mm	EAN 4047728+
①	<b>V5914-1</b>	Adapter 30 mm	–	–	–	–	<b>059510</b>
②	<b>V5914-2</b>	Adapter 86 mm	–	–	–	–	<b>059527</b>
③	<b>V5914-3</b>	Cylinder adapter	–	–	–	–	<b>059534</b>
④	<b>V5914-4</b>	Fixing plate	–	–	–	–	<b>059541</b>
⑤	<b>V5914-11</b>	Pressure sleeve	64.5	52.5	51.2	32	<b>059558</b>
⑥	<b>V5914-12</b>	Pressure sleeve	69.5	57.5	56.2	32	<b>059565</b>
⑦	<b>V5914-13</b>	Pressure sleeve	74.5	62.5	61.2	32	<b>059572</b>
⑧	<b>V5914-14</b>	Pressure sleeve	79.5	67.5	66.2	32	<b>059589</b>
⑨	<b>V5914-15</b>	Pressure sleeve	84.5	72.5	71.2	32	<b>059596</b>
⑩	<b>V5914-16</b>	Pressure sleeve	89.5	77.5	72.2	32	<b>059602</b>
⑪	<b>V5914-17</b>	Pressure sleeve	93.5	81.5	76.7	32	<b>059619</b>
⑫	<b>V5914-21</b>	Pressure pipe	64.5	62	52	100	<b>059626</b>
⑬	<b>V5914-22</b>	Pressure pipe	69.5	67	57	100	<b>059633</b>
⑭	<b>V5914-23</b>	Pressure pipe	74.5	72	62	100	<b>059640</b>
⑮	<b>V5914-24</b>	Pressure pipe	79.5	77	67	100	<b>059657</b>
⑯	<b>V5914-25</b>	Pressure pipe	84.5	82	72	100	<b>059664</b>
⑰	<b>V5914-26</b>	Pressure pipe	89.5	87	73	100	<b>059671</b>
⑱	<b>V5914-27</b>	Pressure pipe	93.5	91.5	88.5	100	<b>059688</b>
⑲	<b>V5914-28</b>	Pressure pipe	110	107	96	100	<b>059695</b>



**V5913**
**EAN 4047728059398**

## Basic set for slotted bushings

- Set for universal crimping of slotted bushings
- Slotted silent blocks must be installed in the beam under pretension
- Using a vice or a hydraulic unit in combination with the included clamping device, the bushing is tensioned before installation
- Thanks to the locking pin, no constant pressure needs to be exerted on the clamping device
- Pressure sleeve set V5914 or V5066 is required to press around the bushing
- The set includes shells for bushings with diameters of: 65, 70, 75, 80, 85 and 95 mm
- Recommended for use with 32-tonne hydraulic cylinder V2874 (not included)



Supplied in Multibox  
V4700-XL!

VIGOR No.	Designation	EAN 4047728+
<b>V5913-1</b>	Clamping piece 95 mm	<b>059404</b>
<b>V5913-4</b>	Bolts	<b>059435</b>
<b>V5913-65</b>	Adapter Ø 65 mm, 2-piece	<b>059459</b>
<b>V5913-70</b>	Adapter Ø 70 mm, 2-piece	<b>059466</b>
<b>V5913-75</b>	Adapter Ø 75 mm, 2-piece	<b>059473</b>
<b>V5913-80</b>	Adapter Ø 80 mm, 2-piece	<b>059480</b>
<b>V5913-85</b>	Adapter Ø 85 mm, 2-piece	<b>059497</b>


**7**
**V5913/6**
**EAN 4047728083263**

## Expansion set for slotted bushings

- To be used in combination with main set V5913
- Set includes shells for slotted bushings with diameters: 50, 56, 58, 60, 63, 68 mm
- Recommended for use with 32-tonne hydraulic cylinder V2874 (not included)



Supplied in Multibox  
V4700-XL!

VIGOR No.	Designation	EAN 4047728+
<b>V5913-50</b>	Adapter Ø 50 mm, 2-piece	<b>087070</b>
<b>V5913-56</b>	Adapter Ø 56 mm, 2-piece	<b>087087</b>
<b>V5913-58</b>	Adapter Ø 58 mm, 2-piece	<b>087056</b>
<b>V5913-60</b>	Adapter Ø 60 mm, 2-piece	<b>087063</b>
<b>V5913-63</b>	Adapter Ø 63 mm, 2-piece	<b>087049</b>
<b>V5913-68</b>	Adapter Ø 68 mm, 2-piece	<b>087094</b>

Installation situation of a slotted and tensioned bushing


**6**



**V8320**EAN 4047728**083201****Bushing set BPW and ROR**

- Bushing set for replacing the 119 mm and 139 mm rubber bushing on **BPW** and **ROR** axles
- Efficient and safe removal and installation of the silent block
- Recommended for use with 32 tonnes hydraulic cylinder V2874 (not included)

  
32t


8


**V4555**EAN 4047728**045551****Wheel hub puller set for trucks · buses and trailers 45 tonnes**

- Wheel hubs of trucks with 8 bolts, 275 mm, or 10 bolts, 335 mm
- Removing wheel hubs with compact bearings e.g. on **SAF** axles
- Sturdy construction facilitates the full power of 45 / 70 tonnes together with impact force when removing the wheel hub

  
45t / 70t


**Article approved  
for impact  
function!**

**Also suitable  
for 70 tonnes!**



VIGOR No.	Designation	EAN 4047728+
<b>V3263</b>	Screw · M22 x 60 mm	<b>032636</b>
<b>V4556</b>	Plate with thread for V3750 · V4554 · V4555	<b>045568</b>
<b>V3222</b>	Pressure foot	<b>032223</b>
<b>V4546</b>	Thrust rod · M30 · length 140 mm · Ø 38 mm	<b>045469</b>
<b>V4545</b>	Thrust rod · M30 · length 30 mm · Ø 38 mm	<b>045452</b>
<b>V4549</b>	Extension · 100 mm · Ø 38 mm for V4555 · V4566	<b>045490</b>
<b>V4547</b>	Extension · 50 mm · Ø 38 mm for V4555 · V4566	<b>045476</b>
<b>V4548</b>	Extension · 70 mm · Ø 38 mm for V4555 · V4566	<b>045483</b>

12



**V4500**

EAN 4047728045001

## Wheel hub puller commercial vehicle · 45 tonnes

- Removal of rusted bearings with outside wheel hubs from straight shafts
- For: **Volvo** FL · TGS · TGX · **MERCEDES-BENZ** Atego · Actros · **RENAULT** Kerax · Magnum · Midlum · Premium
- Can also be used for vehicles with identical construction
- 45- / 70-tonne version




**Can also be used  
with 70 tonnes!**

**Article approved for  
impact function !**



M30 thread



3

**V3750**

EAN 4047728037501

## Wheel hub extractor for low-height trailers

- Removal of 225 mm wheel hub with 10 screws
- Extractor enables loosening of hubs with bearing unit on straight shafts
- Recommended for use with 32 tonnes hydraulic cylinder V2874 (not included)
- Sturdy construction enables pressure up to 45 / 70 tonnes and hammer stroke in direction of pressure



**Article approved  
for impact  
function !**

**Can also be used  
with 70 tonnes!**



15

**V8322**
**EAN 4047728083225**

### Wheel and rim puller for trucks

- Rim puller for efficient and safe removal of stuck wheels/rims
- Quick and effortless removal in just a few minutes
- Three receiving adapters for pressure sleeves in a set for truck, bus and trailer rims: 22.5", 19.5", 17.5"
- Application with an impact wrench, alternating pressure on screw connections
- Four rim hooks fit into most rim ventilation holes
- Saves time and effort, an essential investment for workshops that encounter stuck wheels
- Traditional methods are tedious, dangerous and reduce workshop productivity

#### The rim is loosened in just a few minutes

1. Install the bolt ring
2. Install the mounting rod
3. Install the hook and chain
4. Use an impact wrench to pull the rim off the hub




17

**V3678**
**EAN 4047728036788**

### Brake disc removal (floating) · Volvo · RENAULT · DAF


- Removal of floating brake discs
- Removal of the brake disc by alternately pressing the cylinders
- Two special cylinders and two-way control valves for alternate pressing
- Brake disc removal in just a few minutes



VIGOR No.	Designation	EAN 4047728+
<b>V3678-1</b>	Clutch set extension · 4-piece	<b>087124</b>

**V5907**
**EAN 4047728059206**

### Spare cylinder 14 tonnes





**V4972**

EAN 4047728087179

## Hydraulic lifting tool for trucks

- Lifting aid with high loading capacity (450 kg), which makes lifting heavy loads superfluous. The design offers maximum access and flexibility for ergonomically correct work on trucks, trailers and buses.
- Lifting heavy loads in combination with an incorrect working posture poses a major risk to the working environment and the health of the mechanic. The flexible lifting arm for the press frame provides excellent access when replacing the king pin on the steering knuckle.
- Wheel hub removal is effortless, the powerful hydraulic cylinders (45-tonne V4229 and 70-tonne V8321) are fixed in the supplied tool holder. Wheel hubs with brake discs or brake drums, wheel hubs with dual tyres in combination with brake drums are raised and lowered onto the vehicle without any manual force.
- Thanks to the four large swivel castors, the lifting aid is easy to move and manoeuvre, even with a maximum load of 450 kg. If required, the front wheels can be locked in the straight-ahead position.
- When replacing the king pin etc., the hydraulic pump supplied can be easily removed from the lift truck so that it can be used on the ground. Both practical handles on the rear wheels are very helpful during installation of the hub onto the wheel axle.
- CE-marked product for maximum safety
- ISO 45001 Occupational health and safety management standard in the EU
- The lifting platform can be supplemented with accessories such as a universal device for removing brake callipers and a holder for the press frame when replacing bushes
- Height-adjustable by means of hydraulics.  
Also variable in the basic position via rectangular perforation.



6




**Available from May 2025!**



**New**



Press cylinder holding device



**V7275**

 EAN 4047728**072755**

## Multibox · starter set · wheel bearing of van front axle

- More mobility in the fields of trade, industry and service
- Considerable time savings thanks to usability directly on the vehicle, estimated time per side is approx. 30-40 minutes
- Replacement of the front axle wheel bearing in the following models:
  - CITROËN Jumper
  - FIAT Ducato
  - PEUGEOT Boxer since 2007
  - RENAULT Master
  - NISSAN Interstar
  - OPEL Movano since 2010
  - FORD Transit since 2000
- The 32 tonne cylinder V2874 is required to use the tool set
- Can optionally be extended for rear axle wheel bearings for diverse models of transport vehicles with V7291
- Cylinder not included in delivery


**SUV**  
**Van**


» For components,  
see VIGOR  
main catalogue  
page 395



18


**V7251**

 EAN 4047728**072540**

## Multibox wheel bearing set IVECO Daily

- More mobility in the fields of trade, industry and service
- Replacement of the front axle wheel bearings in the installed condition on IVECO Daily from model year 2014 →
- To be used with 32-tonne hydraulic cylinder V2874
- Alternative use after removal with the aid of a workshop press
- Cylinder not included in delivery


**SUV**  
**Van**


» For components,  
see VIGOR  
main catalogue  
page 394



11






**V7133**
**EAN 4047728071338**

## Compact wheel bearing removal / installation set

- Including multibox
- Operating all compact wheel bearings from Smart to the Sprinter
- Utilised assembly unit V4491 ensures professional installation of the second generation compact wheel bearing
- Contents: Special unit for installing the closed wheel bearing and a universal set for all other compact wheel bearings diameters
- Cost and time savings by eliminating the need to install a new steering knuckle, the subsequent axle alignment and the associated additional work
- Including two V4700-L multiboxes
- Special set for installing the wheel bearing closed at the wheel hub for the following vehicles, among others:  
**MERCEDES-BENZ** V-Class model year 2014 → · Viano model year 2003 → · Vito van model year 2014 → · Sprinter model year 2008 →
- **VOLKSWAGEN** Crafter model year. 2011 →
- Cylinder not included in delivery



» For components,  
see VIGOR  
main catalogue  
page 342



2x



35


**V7154-4**
**EAN 4047728071765**

## Brake disc removal kit

- Separates severely rusted brake discs and those that are stuck to the wheel hubs
- Heavy hammering on the brake disc can cause damage to the wheel bearing
- Transmission of even pressure across the removal tool feet onto the brake disc. The hydraulic cylinder is supported by an adapter piece on the drive shaft screw connection
- Significantly minimises the risk of damage with an even transmission of force to the brake disc from the four feet
- Recommendation: use of a hydraulic cylinder, e.g. V4551 or V2854
- Alternative application with V4699
- Span width: 260 – 330 mm
- Maximum loading capacity: 22 tonnes
- Cylinder not included in delivery



» For components,  
see VIGOR  
main catalogue  
page 345



21



**V7276-2**

EAN 4047728072908

## Mobile work bench with van / SUV specialty tool assortment and hydraulic foot pump


**V7265**


### Ball joint ejector, hydraulic 8.8 t

- For the hydraulic removal of the ball joint pivots on steering tie rods as well as stabilisers, or on steering and brake levers for trucks and buses, with a maximum compressive force of 8.8 t
- Height adjustment 81 and 113 mm as well as adjustable diameter to 42 and 56 mm
- The design optimises access to hard-to-reach areas



### Tractive and compressive hydraulic cylinder 32 t

- Pressure of the hydraulic cylinder may be combined with impact force when using an impact body
- With the correct adapter, drawbars of M 10 to M 22 can be used


**V5058**

### Tractive and compressive hydraulic cylinder 22 t

- With automatic piston return
  - Pressure of the hydraulic cylinder may be combined with impact force when using an impact body.
- Application: e.g. for removing rusted drive shafts

## Including: V2846 Hydraulic pump · pneumatic

- Design including manometer
- For all hydraulic cylinders
- Working pressure: 700 bar
- Hose length: 2.2 m
- Oil tank: 1.3 l
- Non-drip quick coupling




700 bar



1.3 l



2.2 m



Can also be used to store the pump.


**V7261**


### Circlip tool

- Facilitates the removal of frequently rusted circlips on the inside of wheel bearings
- Maximum force and fast removal due to adjusting screw with recesses for a 6.3 = 1/4" ratchet
- Clamping range: 5 – 95 mm
- Includes 2 tips each: Ø 2.5 mm / Ø 3.0 mm / Ø 3.5 mm



### Wheel bearing unit, screwed, removal tool set · universal

- For removing screwed wheel bearings with 3-4 bolts
- SUV / VAN wheel hubs with 6 and 8 stud bolts to 180 mm diameter can be removed via the adjustable crossbar
- For among others: **DODGE · CHEVROLET/GMC · FORD** Ranger model year 2011 →



### Drive shaft press-out device · 6- and 8-hole

- For removing rusted and glued drive shafts directly on the vehicle
- For bolt circle (6 hole) 114–140 mm, (8 hole) 165 to 180 mm
- Removal of drive shaft with 22 t hydraulic cylinder (installation of the impact body enables use of additional force by using a hammer)

### Scrapers

- Removing rust from the outer edge of the brake discs as well as from the brake calliper lining
- For cleaning the contact surface of the counter plate on among others **VOLKSWAGEN T5 / T6**


**V7263**

### Expansion set for wheel bearings on IVECO Daily

- The front wheel bearing can be pressed out using the 32 t hydraulic cylinder **V2874** while installed
- Alternatively, the set can also be used with the workshop press when removed







V7270



## Expansion set for wheel bearing of van rear axle

- Extension kit for changing rear axle wheel bearings on the following vehicles among others: **CITROËN** Jumper, **FIAT** Ducato, **PEUGEOT** Boxer, **FORD** Transit
- Removal of the drive shaft possible using the 5-hole drive shaft tool (bolt circle 119 - 172 mm)
- Items **V2881** and **V2882** are required for individually replacing rear axle wheel bearings. These are included in the starter set for van front axle wheel bearings
- The 32 t hydraulic cylinder **V2874** is required for use



V7273



## Starter set wheel bearing, van front axle

- Allows the wheel bearings to be changed directly on the vehicle with minimum effort using the 32 t hydraulic cylinder **V2874**
- Replacement of the front axle wheel bearing on the following models:  
**CITROËN** Jumper  
**FIAT** Ducato  
**PEUGEOT** Boxer from 2007  
**RENAULT** Master  
**NISSAN** Interstar  
**OPEL** Movano from 2010  
**FORD** Transit from 2000



V7201N



Installation



Removal



## Universal compact wheel bearing removal/installation tool set

- For removing and installing compact wheel bearings with or without circlip
- Adjustability enables use on all types of currently available and future compact wheel bearings



V7267


## Wheel hub puller

- Removal of screwed wheel bearing units with closed wheel hub. The drive shaft does not have to be removed beforehand anymore
- To be used together with wheel bearing / hub tool **V3731** - **V3732** as well as hydraulic cylinder 16-22 t
- Bolt circle 4 and 5-hole: 92-131 mm
- Note: Do not load tool with more than 18 t
- For models with closed wheel hub, among others:  
**OPEL** Insignia model year 2010 →  
**CITROËN** C1 model year 2006 → · Jumpy model year 2016 → · SpaceTourer model year 2016 →  
**PEUGEOT** 108 model year 2015 → · Expert model year 2016 → · Traveller ·  
**TOYOTA** Aygo model year 2006 → · ProAce (Verso) and other models



## Wheel hub/wheel bearing puller for 6 and 8 bolts

- Removing screwed wheel bearings and hub units directly on the vehicle
- Only in conjunction with **V5906**
- No need to remove the drive shaft
- The included M 22 threaded rods connect the tool to one of our hydraulic cylinders
- For bolt circle (6 hole) 111.5 - 142.5 mm, (8 hole) 162.5 - 182.5 mm
- Among others for **MERCEDES-BENZ** Sprinter · X-Class, **NISSAN** Pathfinder, **IVECO** Daily, **VOLKSWAGEN** Crafter, **FORD** F-150 · Ranger



V7133N

## Wheel bearing expansion set for Sprinter / Crafter

- Recommendation: use of a conventional tool set is not possible as a closed wheel bearing is fitted. Drive with a spindle system is not possible
- Special set for installing the wheel bearing closed at the wheel hub for the following vehicles, among others: **MERCEDES-BENZ** V-Class model year 2014 → · Viano model year 2003 → · Vito box model year 2014 → · Sprinter model year 2008 →
- **VOLKSWAGEN** Crafter model year. 2011 →
- Cost and time savings by eliminating the need to install a new steering knuckle, the subsequent axle alignment and the associated additional work
- Prerequisite: Assembly unit for compact wheel bearing **V4491** as well as drive unit, e.g. hydraulic cylinder **V4551** or **V2854**



# PIPE WRENCHES

- Robust cast iron pliers body enables high power transmission
- Quick canting and release on the workpiece due to internal spring
- Coarse jaw serration for optimum grip

## HEAVY DUTY

Continuously adjustable



**New**



Our four pipe wrenches –  
your team with a grip  
on every problem



VIGOR No.	Length mm	Weight kg	EAN 4047728+
<b>V5639-6</b>	130	0.23	<b>086134</b>
<b>V5639-8</b>	170	0.39	<b>086127</b>
<b>V5639</b>	350	1.3	<b>075589</b>
<b>V5639-24</b>	620	3.2	<b>081719</b>

**V6500-190**

EAN 4047728084208

### Heavy-duty diagonal cutter

- High-performance power side cutter for precise and effortless cutting
- Robust construction and sharp cutting blades for clean and precise cuts
- Ergonomically shaped handles for maximum comfort and control during use



**V6504-125**

EAN 4047728082617

### Universal pliers with pushbutton · 125 mm

- Adjustment of the jaw opening at the touch of a button
- Locking of the hinge pin prevents unintentional adjustment
- Jaw opening: up to 44 mm
- Capacity for nuts, size 27 mm
- Capacity for pipes Ø 29 mm / Ø 1"
- Adjustment positions: 15
- Weight: 89 g



**V6504-250**

EAN 4047728077750

### Universal pliers with pushbutton · 250 mm

- Adjustment of the jaw opening at the touch of a button
- Locking of the hinge pin prevents unintentional adjustment
- Jaw opening: up to 65 mm
- Capacity for nuts, size 46 mm
- Capacity for pipes Ø 50 mm · Ø 2"
- Adjustment positions: 23



**V5488**EAN 4047728**054881****Multifunctional drain pan · 50 l**


- Alkaline-resistant and acid-resistant
- Volume: 50 l
- Internal dimensions (W x D x H): 800 x 520 x 100 mm
- From TÜV-certified production in accordance with DIN ISO 16901

**V2234**EAN 4047728**022347****5 kg rubber hammer**

- Loosening rusted rims during a wheel change
- Extra-heavy design for commercial, agricultural and industrial vehicles
- Non-rebound due to steel-ball filling in hammer head (hammer does not rebound)
- Plastic handle
- Dimensions / length: 900 mm
- Hammer head weight: 5 kg

**NITRILE GLOVES****Protects hands from oil, grease, chemicals and dirt**

- Surface structure provides good adhesion, even in oily working conditions
- Safety colour orange for better visibility in dark work spaces
- Comfortable, tear-resistant glove with good dexterity
- Touchscreen compatible
- Material: Nitrile
- Latex- and powder-free



VIGOR No.		Size	EAN 4047728+	
<b>V6436-M</b>	100 pcs./carton	M	<b>080118</b>	
<b>V6436-L</b>	100 pcs./carton	L	<b>077712</b>	
<b>V6436-XL</b>	90 pcs./carton	XL	<b>077729</b>	
<b>V6436-XXL</b>	90 pcs./carton	XXL	<b>077736</b>	

**V4414**EAN 4047728**044141****Oil filter tensioner adjuster · 80 – 115 mm · universal**

- Mechanical locking of the oil filter wrench simplifies subsequent attachment of the reversible ratchet to the oil filter wrench
- The oil filter tensioner adjuster always remains under tension when the reversible ratchet is moved backwards
- Continuously adjustable
- Use with wrench size 21 mm or  $\frac{1}{2}$ " reversible ratchet
- Optimal hold when loosening the oil filter thanks to left-toothed jaws
- For oil filters in areas with restricted access
- Clockwise/anti-clockwise application enables operation of the screw connection
- Drive: 22 mm outside hexagon,  $\frac{1}{2}$ " (12.5 mm) square
- Diameter (min.-max.): 80 – 115 mm

**V4415**EAN 4047728**062114****Oil filter tensioner adjuster · 115 – 140 mm · universal**

- Mechanical locking of the oil filter wrench simplifies subsequent attachment of the reversible ratchet to the oil filter wrench
- The oil filter tensioner adjuster always remains under tension when the reversible ratchet is moved backwards
- Continuously adjustable
- Use with wrench size 21 mm or  $\frac{1}{2}$ " reversible ratchet
- Optimal hold when loosening the oil filter thanks to left-toothed jaws
- For oil filters in areas with restricted access
- Clockwise/anti-clockwise application enables operation of the screw connection
- Drive: 24 mm outside hexagon,  $\frac{1}{2}$ " (12.5 mm) square
- Diameter (min-max): 115 - 140





**V2461N**

EAN 4047728056472

## Socket set

- Drive: solid hexagon 6.3 (1/4 inch), solid hexagon 8 (5/16 inch), hollow square 6.3 mm (1/4 inch), hollow square 10 mm (3/8 inch), hollow square 12.5 mm (1/2 inch)
- Output: E profile, outside hexagon profile, internal wedge profile Ribe-CV, T profile, internal serration profile XZN, inside hexagon profile, Phillips-Recess profile PH, Pozidriv profile PZ, slotted profile, TH profile
- Sizes: · 0.8 x 4 – 1.2 x 7 · 1.3 – 32 · E4 – E22 · PH0 – PH2 · PZ0 – PZ2 · T9 – T30
- For manual operation




172


**V2318N**

EAN 4047728059299

## 3/4" Socket set

- Drive: square 20 mm (3/4 inch)
- Output: outside hexagon profile
- Sizes: 19 – 50
- Number of teeth: 24 (operating angle 15°)
- For manual operation



21


**V5461**


EAN 4047728080323

## Socket set

- For manual operation



12-point  
design



» For components see  
catalogue page 168



133





**V5034/3**EAN 4047728**086318****Impact extension set**

- Material: Cr-Mo
- For impact operation
- Ideal for hard-to-reach places

20 3/4"

**New**

VIGOR No.	Designation	Length mm	EAN 4047728+
<b>V5034-100</b>	Impact extension	100	<b>086349</b>
<b>V5034-200</b>	Impact extension	200	<b>086332</b>
<b>V5034-400</b>	Impact extension	400	<b>086325</b>

3

**V7212**EAN 4047728**072120****Inside hexagon impact screwdriver socket set**

- Common screw connections for VAG vehicles, e.g. brake carriers, central drive shafts, shock absorbers or screwed wheel bearing units
- Drive: 3/4 inch (20 mm) square
- Output: inside serration profile XZN, inside hexagon profile
- Surface: burnished, oiled
- For impact operation

**V5024**EAN 4047728**050241****Impact socket set**

- Extra thin-walled sockets for drive shaft screw connections in the wheel hub
- Adjusted to given spaces in the wheel hub
- Among others for:
  - Size 24: **VW** Touran model year 2006 →
  - Size 30: **VW** Passat C, Golf 4, Polo, New Beetle · **AUDI** TT · **ŠKODA** Octavia, Superb, Fabia
  - Size 32: **VW** Touareg model year 2003 →
  - Size 36: **BMW** 3-series · 5-series · 7-series · **SEAT** Ibiza · **VW** Polo, Golf Plus · **OPEL** Corsa D · Adam · Mokka · **CHEVROLET** Trax model year → 2013 · **FIAT** 500 · Grande Punto · Punto Evo model year → 2005 · **FORD** Ka · **MERCEDES-BENZ** S-Class · **JAGUAR** XJ40 · XJ181
- Drive: 3/4 inch (20 mm) square
- Output: outside 12-point profile
- For impact operation



**V4970**


 EAN 4047728**086219**

## Telescopic ratchet set

- 180° swivel head with locking mechanism
- Quick-release press-button
- For manual operation

**S**

6.3	1/4"	10	3/8"	12.5	1/2"	20	3/4"
6.3	1/4"	10	3/8"	12.5	1/2"	20	3/4"



**New**


**Including extension  
75 and 250 mm!**

**V4970-L**

 EAN 4047728**086110**

## Telescopic ratchet insert S · empty


**New**
**V5010/12**

 EAN 4047728**086981**

## Screwdriver with impact cap · including square

- 2-component handle
- Screwdriver with impact cap
- Square in the impact cap
- Hexagon at the blade



+	-	6.3	1/4"
---	---	-----	------


**New**

VIGOR No.	Designation	EAN 4047728+
<b>V1208</b>	Screwdriver for slotted screws 5.5 x 38	<b>012089</b>
<b>V5010-SL3.5</b>	Screwdriver for slotted screws: 3.5 x 75	<b>086561</b>
<b>V5010-SL5</b>	Screwdriver for slotted screws 5 x 100	<b>086578</b>
<b>V5010-SL6</b>	Screwdriver for slotted screws 6 x 125	<b>086585</b>
<b>V5010-SL8</b>	Screwdriver for slotted screws 8 x 150	<b>086592</b>
<b>V5010-SL10</b>	Screwdriver for slotted screws 10 x 200	<b>086608</b>
<b>V1209</b>	Phillips-Recess screwdriver PH2	<b>012096</b>
<b>V5010-PH0</b>	Phillips-Recess screwdriver PH0	<b>086516</b>
<b>V5010-PH1</b>	Phillips-Recess screwdriver PH1	<b>086523</b>
<b>V5010-PH2</b>	Phillips-Recess screwdriver PH2	<b>086530</b>
<b>V5010-PH3</b>	Phillips-Recess screwdriver PH3	<b>086547</b>
<b>V5010-PH4</b>	Phillips-Recess screwdriver PH4	<b>086554</b>


**12**


**V6050**EAN 4047728**086141****One-hand multifunctional wrench**

- Chrome-vanadium
- Multifunctional wrench with ratchet function
- Automatic adjustment to the screw size
- Wrench sizes: 8 - 17 · 14 - 32
- Self-clamping

**New****V1001/2**EAN 4047728**086752****Impact rod set**

- Diameter 25 mm and 16 mm
- Exchangeable nylon caps
- Impact rod 25 mm with steel ball filling (non-rebound)
- Extension for hammer
- Precise and secure impact possible

**New**

VIGOR No.	Designation	Ø mm	EAN 4047728+
<b>V1001-16</b>	Impact rod	16	<b>086707</b>
<b>V1002-16</b>	Nylon spare cap	16	<b>086738</b>
<b>V1001-25</b>	Impact rod	25	<b>086721</b>
<b>V1002-25</b>	Nylon spare cap	25	<b>086745</b>

**2****MACHINIST'S HAMMER**

- Hickory wood handle
- High-quality hammer with rubber impact protection
- Sturdy design for long-lasting performance and reliability



VIGOR No.	Length mm	Weight g	EAN 4047728+
<b>V2662-300</b>	300	300	<b>084444</b>
<b>V2662-500</b>	320	500	<b>084451</b>
<b>V2662-800</b>	350	800	<b>084437</b>
<b>V2662-1000</b>	360	1000	<b>084420</b>

**V2663-1500**EAN 4047728**084383****Club hammer**

- Hickory wood handle
- High-quality hammer with rubber impact protection





**V7740/6**

EAN 4047728084499

## Combination wrench set XXL

- Chrome-vanadium
- DIN 3113
- Surface: chrome-plated, polished



34 · 36 · 38 · 41 · 46 · 50 mm



6


**V6640**

EAN 4047728085588

## Combination wrench set XXL in soft foam insert

- For contents see V7740/6

L



6


**V7031**

EAN 4047728082624

## Ratcheting box-end wrench set · extra long

- At least 60 % longer than standard ratchet wrenches – for greater power transmission
- Slim design
- Tool roll
- Surface: chrome-plated, polished
- 72 teeth
- 5° operating angle

10 · 11 · 12 · 13 · 14 · 15 ·  
16 · 17 · 18 · 19 mm



10


**V2338**

EAN 4047728023382

## Kneeling mat


- Comfortable working in the workshop, industry, garden or household
- High-quality foam
- Knee-protecting
- Heat insulating
- Water and oil repellent
- With carrying handle
- Dimensions: 475 mm x 235 mm x 26 mm



**V2338-XL**

EAN 4047728071444

## Mechanic's mat

- Comfortable working on the floor in the workshop, industry, garden or household
- Large lying surface
- High-quality foam
- Low-impact
- Pliant and heat-retaining foam
- With two handles
- Dimensions: 980 mm x 480 mm x 27 mm




**V5671N**EAN 4047728**076715****MINI GIANT****1/2" Impact wrench · mini****12<sup>S</sup> 1/2"****1/2"**  
**1200 Nm**

Ø mm	Nm	max. Nm	max. Nm	rpm	kg	l/min.	bar	m/s <sup>2</sup>
12,91 (1/2") 7,2	600	850	1200	10000	1.28	141.5	6.3	6.81

**V6899N**EAN 4047728**076944****GIGA GIANT****3/4" Impact wrench**

*The most  
powerful  
in its  
class!*

**20 3/4"****3/4"**  
**2300 Nm**

Ø mm	Nm	max. Nm	max. Nm	rpm	kg	l/min.	bar	m/s <sup>2</sup>
16,41 (3/4") 7,2	1400	2000	2300	5500	3.60	254.8	6.3	5.75

**V5505N**EAN 4047728**080484****Impact universal joint set**



- Working in areas with restricted access, and for getting around obstructive edges

**3**

VIGOR No.			EAN 4047728+
<b>V5505N-1/4</b>	<b>6.3 1/4"</b>	<b>6.3 1/4"</b>	<b>083324</b>
<b>V5505N-3/8</b>	<b>10 3/8"</b>	<b>10 3/8"</b>	<b>083317</b>
<b>V5505N-1/2</b>	<b>12.5 1/2"</b>	<b>12.5 1/2"</b>	<b>083300</b>

**AIR BLOW GUNS**

- Fast removal and cleaning of chips and other foreign objects
- Long-life aluminium housing
- Suspension device incorporated



VIGOR No.	Design	EAN 4047728+
<b>V7135</b>	Short	<b>071352</b>
<b>V7135-150</b>	Long · tip 150 mm	<b>071369</b>

**V7501-39**


EAN 4047728082037

## Video borescope with Ø 3.9 mm probe


Analysis and documentation of damage patterns in difficult to access spaces!

- Probe: Ø 3.9 mm
- Probe length: 1000 mm
- Camera resolution: 1280 x 720 (corresponds to HD quality)
- Camera viewing angle: 80°
- 6 dimmable LEDs
- Depth of field: 20 – 80 mm
- 5" display, swivelling
- Display resolution: 1280 x 720 pixels
- 6 Ah, 3.7 V Li-ion rechargeable battery
- 2A/5V power supply unit, USB charging cable and 32 GB TF memory card included in delivery

Screen can be moved freely in all directions



Swivels 180° on both sides





# Your tool deserves a better home!

Find the perfect empty tool trolley for your needs.  
Individual just like you! You decide. Come and snap up the perfect model for you!

## Series M – Small but mighty

**VIGOR**  
SERIES **M**
**400 kg**

Total loading capacity

**20 kg**

L: 681 mm  
W: 460 mm  
H: 1016 mm


**20 kg**  
7 x


**5 kg**  
5 x  
569 x 398 x 75 mm


**5 kg**  
569 x 398 x 154 mm

**V5489**

EAN 4047728**054898**

Price with foam mat



## Series L – The all-rounders

**VIGOR**  
SERIES **L**
**500 kg**

Total loading capacity

**25 kg**

L: 733 mm  
W: 481 mm  
H: 1002 mm


**STAINLESS STEEL**
**25 kg**  
8 x


**7 kg**  
7 x  
569 x 398 x 75 mm


**1 kg**  
569 x 398 x 154 mm


**25 %**

25% more drawer capacity compared to Series M

**V1901**

EAN 4047728**019019**

Price with plastic worktop

Price with stainless steel worktop



## Series XL – Bigger is better

**VIGOR**  
SERIES **XL**
**500 kg**

Total loading capacity

**25 kg**

L: 949 mm  
W: 523 mm  
H: 1017 mm


**STAINLESS STEEL**
**25 kg**  
8 x


**7 kg**  
7 x  
753 x 398 x 75 mm


**1 kg**  
753 x 398 x 154 mm


**33 %**

33% more drawer capacity compared to Series M

**V4481**

EAN 4047728**044813**

Price with plastic worktop

Price with stainless steel worktop



## Series XD – The space saving boss

**VIGOR**  
SERIES **XD**
**500 kg**

Total loading capacity

**30 kg**

L: 986 mm  
W: 695 mm  
H: 1017 mm


**STAINLESS STEEL**
**30 kg**  
8 x


**7 kg**  
7 x  
790 x 570 x 75 mm


**1 kg**  
790 x 570 x 154 mm


**53 %**

53% more drawer volume compared to Series XL

**V4481-XD**

EAN 4047728**066488**

Price with stainless steel worktop



## Series XXL – For everything big

**VIGOR**  
SERIES **XXL**
**1000 kg**

Total loading capacity

**30 kg**

L: 1615 mm  
W: 686 mm  
H: 1035 mm


**STAINLESS STEEL**
**60 kg**  
3 x



**30 kg**  
10 x


**60 kg**  
Monster drawer

**V4481-XXL**

EAN 4047728**080491**

Price with stainless steel worktop





With stainless steel worktop

**Tool trolley  
available with  
assortment  
1 or 2!**

Drawers:

- 7x flat
- 1x high

L x W x H  
723 x 459 x 1002 mm



With plastic worktop

**Tool trolley  
available with  
assortment 2!**

Drawers:

- 6x flat
- 2x high


L x W x H  
723 x 459 x 1002 mm

## ASSORTMENT 1 Including tool trolley with stainless steel worktop


V4188



V4753



V6724N



V5006

V5017

V4995



V5068

V4991

V5070



V5004

V5072

V5633N



V6811



**442**  
tools including  
tool trolley


VIGOR No.		Designation	kg	EAN 4047728+
V1901-X/442	442	Tool trolley with stainless steel worktop and assortment 1	131	084338

## ASSORTMENT 2 Including tool trolley with stainless steel or plastic worktop


V4188



V4753



V6724N



**376**  
tools including  
tool trolley

V5068

V5070

V5006



V5633N

V5603

V7324



VIGOR No.		Designation	kg	EAN 4047728+
V1901-X/376	376	Tool trolley with stainless steel worktop and assortment 2	119	084192
V1901/376	376	Tool trolley with plastic worktop and assortment 2	100	080293



**V4813/NKW**

EAN 4047728085687


## Work bench advantages

- Robust wooden worktop
- Vice V6150N can be screwed on (not included in delivery)
- Door allows large tools to be stowed away
- Including 7 inserts

**+7  
inserts!**



L x W x H  
1091 x 481 x 1018 mm



**Our tip!**  
Vice  
V6150N



**V1901-X/NKW**

EAN 4047728085601


## Tool trolley advantages

- Compact design
- Saves a lot of space in the workshop
- Stainless steel worktop: resistant to dirt
- Including 7 inserts

**+7  
inserts!**



L x W x H  
723 x 459 x 1002 mm



**Our tip!**  
Laptop table  
V6221



## Both tool trolleys come with 7 inserts!

L

**2  
K**


## Advantages of inserts

- 3/4" socket set for heavy-duty use (V5109)
- XXL Combination wrench as problem solver (V6640)
- Fine-tooth solid steel ratchets for use on commercial vehicles



19 · 21 · 22 · 23 · 24 · 26 · 27 · 28 · 30  
32 · 34 · 36 · 38 · 41 · 46 · 50 mm

34 · 36 · 38 · 41 · 46 · 50 mm








With stainless steel worktop

**Tool trolley  
available with  
assortment  
1, 2 or 3!**








With plastic worktop

**Tool trolley  
available with  
assortment  
1 or 3!**



Edge protection

## ASSORTMENT 1 Including tool trolley with stainless steel or plastic worktop



# 499

tools including  
tool trolley

VIGOR No.	XX	Designation	kg	EAN 4047728+
V4481-X/499	499	Tool trolley with stainless steel worktop and assortment 1	150	062367
V5434	499	Tool trolley with plastic worktop and assortment 1	141	054348

## ASSORTMENT 2 Including tool trolley with stainless steel worktop

V4586



V6650N



V7015N



V6015



V5170



# 466

tools including  
tool trolley




VIGOR No.		Designation	kg	EAN 4047728+
V4481-X/466	466	Tool trolley with stainless steel worktop and assortment 2	140	074674

## ASSORTMENT 3 Including tool trolley with stainless steel or plastic worktop

V4586



V6650N



V5170



V5638N



# 375

tools including  
tool trolley

VIGOR No.		Designation	kg	EAN 4047728+
V4481-X/375	375	Tool trolley with stainless steel worktop and assortment 3	127	062350
V4542	375	Tool trolley with plastic worktop and assortment 3	117	045421








# The space saver!

» With stainless steel worktop

» Drawer slide out 100 %

**EXTRA DEEP!**



**775**  
tools including  
tool trolley

VIGOR No.		Designation	kg	EAN 4047728+
<b>V4481-XD/775</b>	775	Tool trolley with stainless steel worktop and assortment	210	<b>068529</b>



LD

XD

XXD

**VIGOR**  
 SERIES **XXL**

# In a class of its own!

» With stainless steel worktop

» Drawer slide out 100 %



## EXTRA DEEP + EXTRA WIDE!


L x W x H  
1625 x 695 x 1017 mm

V6830



V6831

V6807N

V6808N



Discover a new dimension of reality! »



Including socket strip with 2x USB and 2x USB-C as well as 2-metre H07 cable with safety plug



# 929 +

tools including tool trolley



Including can holder V2393-XD



VIGOR No.



Designation



EAN 4047728+

V4481-XXL/929

929

Tool trolley with stainless steel worktop and assortment


296

082303

## FOR SCREWING


**V6221**, EAN 4047728062213

Laptop table




**V6393**, EAN 4047728069519

Document holder




**V6395**, EAN 4047728070522

Waste bin




**V6398**, EAN 4047728071314

Laptop holder · rotatable and pivotable



**V6393-S**, EAN 4047728069205


Document holder · small



## MAKE YOUR TOOL UNIQUE!


**V6396**, EAN 4047728069601

Screwdriver holder




**V2397**, EAN 4047728023979

Holder for paper reel




**V6394**, EAN 4047728069595

Impact wrench holder




**V6397**, EAN 4047728069793

Holder for paper reel · pivotable




**V2393**, EAN 4047728023931


Can holder




# TO HOOK ONTO PERFORATED TOOL PANEL PLATE 9 x 9 mm



Perforated tool panel plate for tool trolleys



V6399




V6399-XD

VIGOR No.	Designation	EAN 4047728+
<b>V6399</b>	For Series M, L and XL	<b>085533</b>
<b>V6399-XD</b>	For Series XD and XXL	<b>085540</b>

**V6000-059**, EAN 4047728085557


Cordless tool holder




## TROLLEY

**V6000-055**, EAN 4047728077118

Torque wrench holder

**V6000-055XL**, EAN 4047728077125

Torque wrench holder · large




Tool hook set

**V2517**


EAN 4047728025171

**V2518**

EAN 4047728025188

**V2519**


EAN 4047728025195

**V2520**


EAN 4047728025201

**V6000-060**, EAN 4047728085526

Glove box holder

**V6150N**, EAN 4047728084734

Vice





# Whether on your tablet, laptop or computer. Start configuring now!




[www.vigor-equipment.com/konfigurator](http://www.vigor-equipment.com/konfigurator)

Click here for the  
KonVIGORator



## New functions

- **Augmented Reality\*:** Besides the new 3D function, our KonVIGORator now has the option of "placing" your planned wall unit directly where you want it! All you need is a mobile phone or a tablet with a camera. You can either configure directly on your mobile device or relaxed on your computer and then scan the QR code.
- **Availability display:** Now you can already see whether an item is available when configuring it



\*Latest system software required



## Our 700 mm depth now offers you even more storage space!

In the current system, the 500 mm cabinets are extended to 700 mm with our extension frames and thus offer you even more working space.

Our new lower cabinets from the XD family now offer you even more lower cabinet space – namely the full 700 mm! More space for tools, small parts and much more!

We start with our three most popular lower cabinets. If you like the new system as much as we do, more cabinets will follow – so stay tuned!


PS.: Of course, you can also find the new lower cabinets in the KonVIGORator!




## OUR STARTER KIT

### Storage system


- 3-module combination in wide design
- Available with wooden or stainless steel worktop
- Including side veneer



Also available with wooden worktop!



Feet adjustable  
in height to 50 mm




VIGOR No.	Designation	EAN 4047728+
<b>V6000-3P1XL</b>	Storage system combination · starter kit · wooden	<b>073318</b>
<b>V6000-3P1XL-X</b>	Storage system combination · starter kit · stainless steel	<b>073271</b>

## OUR COMPLETE KIT

### Storage system


- 3-module combination in wide design with perforated panel structure and wall cabinets
- Available with wooden or stainless steel worktop
- Including side veneer




Feet adjustable  
in height to 50 mm



**Configure your  
storage system  
now!**



Also available with wooden worktop!



VIGOR No.	Designation	EAN 4047728+
<b>V6000-3P2XL</b>	Storage system combination · complete kit · wooden	<b>073301</b>
<b>V6000-3P2XL-X</b>	Storage system combination · complete kit · stainless steel	<b>073295</b>



# Powerful variant! 3.5 kW

**V4891-3.5**

EAN 4047728072779

## Induction heater · 3.5 kW

- Modern and efficient heating – prevents damage to surrounding components
- Targeted heating within seconds
- Cooling fluid and focus coil included in delivery
- Water cooling up to the coil head
- Avoidance of overheating thanks to integrated ventilator
- Extensive accessories for various application fields
- Highest possible capacity in compact design • Output power can be precisely adjusted for the application field – from 10 – 100%
- Operating information via LED display on the handle

**3.5 kW**



Coils optionally available, not included in delivery.

2

